

DG Series High Capacity Force Gauge

The CHATILLON® DG Series mechanical force gauge is ideal for a wide range of force testing applications up to 500 lbf ($2.5 \, \text{kN}$). Based on our popular DPPH Series force gauge, the DG Series features a larger, 2.25-inch dial for improved resolution and readability, peak hold button, durable plastic housing, universal mounting plate, ergonomic shape and improved accuracy of $\pm 0.5\%$ of full scale. The DG gauge is an excellent, economical solution for tensile or compression testing.

The DG Series may be used as a hand-held device or equipped with an optional handle set for two-hand operation. It is ideal for test stand applications, and when combined with the MT500 Series mechanical test stand, offers you a versatile, economic test sytem with a capacity of up to 500 lbf (2.5 kN).

The DG Series features an an easy to read concentric dial that measures clockwise only. Dial rotates 360-degrees for taring. A peak hold switch captures peak readings and can be easily and quickly returned to zero. A mechanical overload feature protects the gauge from damage. Available in lbf, kgf or N units of measure. DG Series gauges come complete with protective carrying case and a set of stainless steel attachments. A Certificate of Calibration with NIST Data is supplied standard.

FEATURES

- Easy to Use, Durable Construction
- Tensile or Compression Testing
- Intrinsically Safe
- Capacities Up to 500 lbf (200 kgf, 2.5 kN)
- Push or Pull Operations
- Tare Ring
- Peak Capture
- Universal Mounting Plate
- NIST Calibration with Data

SPECIFICATIONS

Accuracy: ±0.5% of Full Scale
Overload Capacity: 110% of Rated Capacity
Maximum Overload: 150% of Rated Capacity
Tare Capacity: 10% of Rated Capacity
Dial Resolution: 0.5% of Full Scale

Deflection: 10mm (.394 inches) at Full Scale Operating Temperature: +40°F to +110°F (+5°C to +45°C)

Instrument Weight: 4.7 lbs (2.12 kg)
Shipping Weight with case: 8.4 lbs (3.80 kg)
Warranty: 2 Years









SS-FM-3002-0503

May 2003

DIMENSIONS 2.7" [68.6mm] 1.0" [25.4mm] — 4.45" -[113mm] 0.6" [15.2mm] 7 [68.6mm] 0 ø2.2" [ø55.9mm] 9.5″ [241mm] 5.0" [127mm] 11.0" [279mm] -#10-32 UNF Mtg Holes (4 Places) -5/16-18 UNC 0.38" [9.5mm] Long Both Ends \forall -1.75″ - [44mm] L_{1.0"} [25.4mm] E96-331 -3.85



DG Series force gauge shown with optional Handle Set Assembly (p/n SPK-DG-Handle).



Optional Handle Set Assembly (p/n SPK-DG-Handle).

ORDERING INFORMATION

Decimal Dials (LBF)

Model	Capacity x Resolution
DG-200	200 x 1.0 lbf
DG-300	300 x 1.5 lbf
DG-400	400 x 2.0 lbf
DG-500	500 x 2.5 lbf

Decimal Dials (KGF)

Model	Capacity x Resolution
DG-100KG	100 x 0.50 kgf
DG-250KG	250 x 1.25 kgf

S.I. Dials (Newtons)

Model	Capacity x Resolution
DG-1000N	1000 x 5.0 N
DG-2500N	2500 x 12.5 N

ACCESSORIES

Standard Accessories

Part No.	Description
SPK-FMG-008C	Chisel Point
SPK-FMG-009B	Point
SPK-FMG-010B	Notch
SPK-FMG-011B	Flat
SPK-FMG-012C	Hook, Stationary
SPK-FMG-013B	Extension Rod, 6-inch
NC002728	Carrying Case
NC002737	Operator's Manual

Optional Accessories

Part No.	Description
ML3868	Hook, Swivel
NC002500	Hook, with Clasp
SPK-DG-Handle	Handle Set Assembly
SPK-DG-TCM-TCD	Adapter, TCM/TCD Stand
SPK-DG-HTC	Adapter, HTC Stand
SPK-DG-TT	Adapter, TT Tester
SPK-MT-0005	Adapter, MT Stand

Itin Scale Co., Inc. 431 Avenue U Brooklyn, NY 11223 PHONE: 718-336-5900 FAX: 718-627-1313

EMAIL: sales@itinscales.com

www.itinscales.com